

MUSCLECRAFT – 2012

200 SPEEDSTER®



Grab up to six of your velocity-obsessed friends, jump into the 200 Speedster model and get ready to zoom from zero to 30 mph (48.3 km/h) in 2.9 seconds, reach 66 mph (106.2 km/h) top speed, then stay there.¹ It displays phenomenal handling and coupled with its low, sleek build, it leaves pretty much everything else behind.



Bright White

HIGHLIGHTS

- Twin 1.5 l supercharged high output Rotax® 4-TEC® engine
- Swim platform with 2-step ladder
- Sunpad
- Ski pylon – pull-up
- Cockpit courtesy lights
- Ski storage
- Satellite-ready AM/FM stereo with MP3 port and 4 speakers
- Depth finder
- 12 volt jack
- Windscreen with pop-up wind deflector and helm storage
- Built-in cooler
- Multi-function aluminum black rails
- Grab handles
- Console storage

SPECIFICATIONS

DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight: No tower.....	2,770 lb / 1,256 kg
With tower.....	2,830 lb / 1,284 kg
Seating capacity.....	7
Fuel capacity	44 gal / 166.5 l

ENGINE

Model	Fuel injected, 1503 Rotax 4-TEC
Type	Twin 1.5 l supercharged high output



Full instrumentation dash, including depth finder



Ski pylon – pull-up



Dual access rear storage



Stereo system with MP3 port



Large cockpit area



Folding tower (optional)

¹ Based on BRP internal testing

CLCS

OVERALL SPECIFICATIONS

DIMENSIONS

Length	19' 9" / 6.02 m
Beam	8' / 2.44 m
Draft	12" / 30.5 cm
Dry weight:	
No tower	2,770 lb / 1,256 kg
With tower	2,830 lb / 1,284 kg
Storage capacity	46 cu ft / 1.3 cu m
Seating capacity	7
Weight capacity	1,365 lb / 619 kg
Fuel capacity	44 gal / 166.5 l

DIMENSIONS (ON TRAILER)

Length [tongue folded]	22' 7" / 6.88 m [20' 6" / 6.25 m]
Width	8' 6" / 2.59 m
Height:	
No tower	6' 6" / 1.98 m
Tower down	7' 1" / 2.16 m
Tower up	9' 11" / 3.02 m
Gross weight:	
No tower	4,095 lb / 1,857 kg
With tower	4,115 lb / 1,885 kg

ENGINE

Model	Fuel injected, 1503 Rotax 4-TEC
Displacement	1,494 cc
Type	Twin 1.5 l supercharged high output
Cylinders (/engine)	3
Max RPM (/engine)	8,000
Fuel type	87 octane – minimum 91 octane – recommended
Emission level	CARB 3-Star
Cooling system	Closed-Loop Cooling System

200 SPEEDSTER



ELECTRICAL

Generator	30 amp / 380 W
Battery	12 V

HULL & DECK

Material	Composite FRP
Vinylester barrier layer	Std
Full fiberglass stringer	Std
Deadrise	21°
Graphics	Std
Color	Bright White

PROPULSION

Jet pump type	Axial flow	Single stage
Impeller:	Material	Stainless steel
	Outside diameter (mm)	159 ± .07
Reverse system		Std

EQUIPMENT

HULL & DECK

- Cleats – chrome (6)
- Cup holders (6)
- Rub rail – Black
- Grab handles (9)
- Navigation lights
- Courtesy lights (3)
- Ski pylon – pull-up
- Tow hooks – stainless steel
bow & stern
- Reboarding ladder – stern (2-step)
- Engine blower (2)
- Automatic bilge pump

STORAGE

- Anchor locker
- In-floor – lockable
- Under seat
- Under Sunpad – lockable
- Glove box – lockable
- Console storage – lockable

CONTROL STATION

HELM

- Steering – Standard with rack and pinion
- Horn
- Separate shift & throttle lever
- Neutral lock
- Battery switch
- Security system D.E.S.S. magnetic lanyard key

CONTROL STATION (CONT.)

INSTRUMENTATION

- Gauges – backlight & anti-fog
- Fuel level
- Tachometer
- Speedometer
- Depth finder
- Overheat

COCKPIT

- Dash finish – Pearlstone
- Outlet – 12 volt accessory (1)
- Cooler – integrated

SEATING

- Driver Seat
- Track & swivel
- Passenger Seat
- Track & swivel

STEREO & SOUND

- Stereo system – satellite-ready
- Speakers – cockpit (2) and bow (2)
- MP3 port

CANVAS & MISCELLANEOUS

- Sunpad
- Wind deflector
- Warranty (1 yr)

CERTIFICATIONS

- NMMA
- CMMA

TRAILER^o

- Single axle
- Disc brakes
- Swing-away tongue

OPTIONS

- Wakeboard tower – foldable
- Wakeboard racks
- Carpet – snap-in
- Mirror – with tower only
- Mooring cover
- Bimini top
- Galvanized trailer with disc brakes
- Fire extinguisher
- Anchor
- Warranty – B.E.S.T. (3 years)

