



## 562 XP®

Husqvarna 562 XP® is developed for professional loggers, tree care workers and skilled land owners. The saw has a ground breaking design and is loaded with innovative solutions for efficient, convenient operation with large air filter and the ability to fit 28" bars. Our unique X-Torq® engine technology provide more power where you need it, up to 20% less fuel consumption and 75% less exhaust emission.



### X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



### REVBOOST™

Rapid acceleration and higher chain speed for best limbing performance.



### AIR INJECTION

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.

## Features

- Easy refueling with flip-up cap
- LowVib® sparing the user's arms and hands
- Fast acceleration
- Adjustable chain oil pump
- Quick-release air filter
- Intuitive, combined choke/stop control
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Easy to maintain with snap locked cylinder cover
- Maximum durability for tough applications
- Smart Start® for easy starting
- Easy and convenient to handle in any situation.
- Felling marks for correct felling direction
- Fuel level window
- Fuel pump for easy starting
- The retaining function prevents losing the bar nuts.
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	3.65 cu.inch / 59.8 cm <sup>3</sup>
Power output	4.7 hp / 3.5 kW
Maximum power speed	9600 rpm
Fuel tank volume	21.98 fl oz / 0.65 lit
Fuel consumption	494 g/kWh
Idling speed	2800 rpm
Spark plug	NGK CMR6H
Electrode gap	0.02" / 0.5 mm
Torque, max.	3.65 Nm / 8100 rpm
Oil tank volume	0.7 US pint / 0.35 lit
Oil pump type	Adjustable flow
Equivalent vibration level (ahv, eq) front / rear handle	2.4 / 3.1 m/s <sup>2</sup>
Sound pressure level at operators ear	106 dB(A)
Sound power level, guaranteed (LWA)	118 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	15"-28" / 38-71 cm
Chain speed at max power	69.9 fts / 21.3 m/s
Chain speed at 133% of maximum engine power speed	92.85 fts / 28.3 m/s
Weight (excl. cutting equipment)	13.01 lbs / 5.9 kg

### ARTICLES

966 57 03-05

966 57 03-07

966 57 03-03

966 57 03-15

966 57 03-11

966 57 03-23

966 57 03-12

966 57 03-10

966 57 01-02      18" - 3/8" - 58GA

