





## T540 XP®

Husqvarna T540 XP® is designed for the high-end top handle saw segment, targeting professional customers like full pro arborists, landscapers, garden contractors and utility services who need excellent performance in combination with the best ergonomics.



### AUTOTUNE

AutoTune gives optimal engine performance throughout automatic engine setting. No time spent on carburettor adjustments. It compensates for different fuels, altitude, humidity, temperature and clogged air filter.



### X-TORQ®

Deliver lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### INDIVIDUAL GRIP SIZE

The top handle grip size can be set in three alternative sizes, to perfectly fit your hand.



### BELT EYE LET

Makes it quick and easy to connect the saw to the climbing harness.

## Features

- The light and strong TechLite  bar makes the saw easier to manouvre.
- Auto return stop switch for easy starting
- Less filter cleanings with Air Injection
- LowVib® sparing the user's arms and hands
- Quick-release air filter
- Adjustable chain oil pump
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Good visibility hand guard
- Fuel level window
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

## Technical data

Cylinder displacement	2.3 cu.inch / 37.7 cm <sup>3</sup>
Power output	2.4 hp / 1.8 kW
Maximum power speed	10200 rpm
Fuel tank volume	11.5 fl oz / 0.34 lit
Fuel consumption	464 g/kWh
Idling speed	3000 rpm
Spark plug	NGK CMR6H
Electrode gap	0.02" / 0.5 mm
Torque, max.	1.79 Nm / 9000 rpm
Oil tank volume	0.42 US pint / 0.2 lit
Oil pump type	Adjustable flow
Equivalent vibration level (ahv, eq) front / rear handle	3.1 / 3.2 m/s <sup>2</sup>
Sound pressure level at operators ear	104 dB(A)
Sound power level, guaranteed (LWA)	116 dB(A)
Chain pitch	3/8"
Recommended bar length, min-max	12"-16" / 30-40 cm
Chain speed at max power	63.65 fts / 19.4 m/s
Chain speed at 133% of maximum engine power speed	84.65 fts / 25.8 m/s
Chain gauge	0.05"
Weight (excl. cutting equipment)	8.6 lbs / 3.9 kg

### ARTICLES

966 61 10-14	14" , US, CAN
966 61 10-16	16" , US, CAN
966 61 10-01	Engine - EPA - US, CAN

